

접 수 번 호 : 25-041150-01-1
(Receipt No.)



안전확인신고 증명서

Confirmation Letter of Declaration

신 고 번 호 : ZU10454-25008
(Application No.)

신 고 회 사 명 : SuZhou MEAN WELL Technology Co., Ltd.
(Applicant)

주 소 : No.269, ChangPing Road, Huangdai Town, Xiangcheng District,
(Address) Suzhou, China

제 품 명 : 컴퓨터용 전원공급장치(Switching Power Supply)
(Product)

기 본 모 델 명 : XDR-960E-48
(Basic Model)

파 생 모 델 명 : See the attachment 2
(Series Model)

정격/안전기준상의 모델구분 : Input: 200-240 Vac, 6.0 A, 50/60 Hz;
(Rating) Output: 48 Vdc, 20 A; Vo Adj.: 48-55 Vdc, Max. 960 W;

안 전 기 준 : KC62368-1(2021-08)
(Standard)

본 확인신고는 제 조 국 명 : 중국

제조업자 명 : SuZhou MEAN WELL Technology Co., Ltd

제조공장의 주소 : No.269, ChangPing Road, Huangdai Town, Xiangcheng District, Suzhou, China

다수 공장의 명 : “이면기재” 의 제품에만 해당함

「전기용품 및 생활용품 안전관리법 시행규칙」 제28조제1항, 같은 조 제3항, 제29조제2항 또는 제34조제2항에 따라 안전확인신고 증명서를 발급합니다.

We issue this Confirmation Letter of Declaration of the Safety Confirmation for the above appliance in accordance with the Article 28(1), 28(3), 29(2) or 34(2) of the Enforcement Rule of the Electrical Appliances and Consumer Products Safety Control Act.

2025 년 07 월 10 일
Year month day

한국산업기술시험원장
KOREA TESTING LABORATORY



※ 이 신고증명서는 「전기용품 및 생활용품 안전관리법」에 따른 제품의 안전성 확인에 한정된 것이며, 그 밖의 다른 법률이 적용되는 제품의 경우에는 해당 법률에 따라 추가로 인증·허가 등을 받아야 합니다.

첨부서류

1. 전기용품의 안전관리부품 및 재질목록(List of Critical Components)(전기용품에 한정한다)
2. 기본모델·파생모델의 내용(Description of the basic and series model)
3. 안전확인신고 내용의 변경 현황(Revisions Status)

안전인증 및 자율안전확인을 받은 자의 유의사항

Notification for recipient (license holder) of Safety Certification and Confirmation Letter of Declaration

1. 본 인증서 또는 신고증명서는 기재된 제조공장에서 생산된 제품으로서 적용된 안전기준에 적합한 경우에 한하여 유효합니다. (This certificate or confirmation letter of declaration is valid only when the product meets the applied safety standard(s) and is manufactured from the manufacturing factory that appears on this certificate.)
2. 안전인증 또는 안전확인 마크는 본래의 의미와 다르게 사용자가 오해를 일으킬 수 있는 방법으로 광고, 카탈로그 등에 사용하면 인증정지 또는 취소의 사유가 됩니다. (Termination or cancellation of the certification may occur if the actual meaning of this safety certification mark(KC-mark) or Confirmation Letter of Declaration mark(KC-mark) is misled to the public by false advertisement on a overstated catalog of the product.)
3. 다음과 같은 사유가 발생할 경우에는 사유가 발생한 날로부터 15일 이내에 안전인증기관에 안전인증 또는 안전확인 변경 신청을 하여 안전인증서 또는 안전확인신고 증명서를 재교부 받아야 합니다. (In case of the following events, this safety certificate or Confirmation Letter of Declaration shall be reapplied within 15 days from the events and reissued for revision.)
 - 1) 제조업자, 수입업자, 주소 등 인증서 기재내용의 변경 (Revision in contents of the certificate such as factory name, importer, factory address, etc)
 - 2) 파생모델의 추가, 변경 또는 삭제 (Adds, changes, or removals of derivative(minor series) model)
 - 3) 안전관리부품의 변경 또는 추가 (Adds or changes in critical components list)
 - 4) 인증서 또는 신고증명서의 분실 또는 훼손 (Losses or damages to this certificate or confirmation letter of declaration)
4. 안전인증 또는 안전확인을 받은 자는 다음 사항을 이행하여야 합니다. (The recipient (license holder) of safety certification (KC-mark) or confirmation letter of declaration shall comply with the followings.)
 - 1) 안전인증표시 등 인증요건의 유지 관리 (Maintaining and managing the marking of safety certification and other certification requirements)
 - ※ 안전인증을 받기 이전 또는 정지, 취소된 이후 생산된 제품에 안전 표시를 하면 법에 의거 처벌을 받게 됨 (It will be punished by the Act if the certification mark is used before the issue (or after suspension or cancellation) of the certification)
 - 2) 자체검사의 실시 및 그 기록관리 (Self Product Verification and record keeping)
 - ※ 안전인증을 받은 자는 제품검사를 철저히 실시하여 제품의 품질이 안전기준에 미달되지 않도록 유의 (Recipients (license holder) of the safety certification (KC-mark) shall conduct products inspection strictly for products to comply with the safety standard.)
5. 안전인증을 받은 자는 전기용품 및 생활용품 안전관리법 제7조 1항 및 동법 시행령 제9조에 의거 2년에 1회 정기검사를 받아야 합니다. (Recipients (license holder) of the safety certification (KC-mark) shall receive routine (regular) factory inspection once every two years according to the Electrical Appliances and Consumer products Safety Control Act article 7(1) and article 9 of Enforcement decree of the same Act.)

(연락처: 인증융합센터, Tel 055-791-3400, 3401)
(Contact point: Certification Evaluation Center Tel: +82 55 791 3400, 3401)

다수 공장의 현황
(The status of Multiple Factories)

No	현황	
1	다수 공장의 명 (Name)	Yongden Technology Corporation
	주소 (Address)	345 MacArthur HighWay, Tabang, Guiguinto, Bulacan 3015, Philippines
	제조국명 (Origin)	필리핀
2	다수 공장의 명 (Name)	MEAN WELL INDIA ELECTRONICS PRIVATE LIMITED
	주소 (Address)	9C, Peenya industrial area, Chokkasandra, 2ND PHASE, PEENYA, Bengaluru (Bangalore) Urban, Karnataka, 560058, India
	제조국명 (Origin)	인도
3	다수 공장의 명 (Name)	MEAN WELL (Guangzhou) Electronics Co.,Ltd.
	주소 (Address)	No.11 Jingu South Road, Huadu District, Guangzhou 510890, Guangdong, China
	제조국명 (Origin)	중국
4	다수 공장의 명 (Name)	MEAN WELL ENTERPRISES CO., LTD.
	주소 (Address)	No. 28 Wuquan 3rd Road, Wugu District, New Taipei City 248, Taiwan (R.O.C.)
	제조국명 (Origin)	대만

☐ 첨부 1 : 전기용품의 안전관리부품 및 재질목록
List of Critical Components

부품명(회로기호) Component(Part no.)	제조사(상표명) Manufacturer(Brand)	모델명(형식) Model(Type)	정격 또는 특성 Rating or Characteristics	인증마크 Tested by
Printed Wiring Board	Interchangeable	Interchangeable	Min. V-1, Rated 130 °C	UL
Input and output Terminal Block (TB1, TB2)	Switchlab Inc	MH140	35 A, 600 V, 115 °C	TUV SUD
(Alternate)	DEGSON TECHNOLOGY CO., LTD.	DG637	30 A, 600 V, 120 °C	VDE
(Alternate)	Dinkle Enterprise Co., Ltd.	EPK635VN	600 V, 35 A, 105 °C	VDE
(Alternate)	Switchlab Inc	MPX332H	Min. 25 A, 600 Vac, 110 °C	TUV SUD
(Alternate)	Switchlab Inc	MPX410	Min. 25 A, 600 Vac, 115 °C	TUV SUD
Fuse (FS1)	Conquer Electronics Co., Ltd.	UBM	F10 A, 250 Vac	VDE
(Alternate)	Conquer Electronics Co., Ltd.	UBM-A	F10 A, 250 Vac	VDE
(Alternate)	Walsin Technology Corp	FSC/FSC(P)	F10 A, 250 Vac	VDE
(Alternate)	Xiamen Set Electronics Co.,Ltd	SCF520P	F10 A, 250 Vac	TUV
(Alternate)	HOLLYLAND CO LTD	5HF(P)	F10 A, 500 Vac	TUV
(Alternate)	HOLLYLAND CO LTD	50CF	F10 A, 500 Vac	TUV
X Capacitor (C1, C2) (Optional)	Kemet Electronics Italia Srl	R.46	Max. 0.68 µF, min. 275 Vac min. 110 °C Class X2	ENEC
(Alternate)	Joey Electronics (Dong Guan) Co., Ltd.	MPX	Max. 0.68 µF, min. 300 Vac min. 110 °C Class X1 or X2.	VDE
(Alternate)	TDK (Zhuhai FTZ) Co., Ltd.	B3292#C/D/T/S/H/J3 series	Max. 0.68 µF, min. 305 V, min. 110 °C Class X2	ENEC
(Alternate)	Liow Gu Electronics Industry Co., Ltd	GS-L	Max. 0.68 µF, min. 250 Vac, min. 110 °C Class X2.	ENEC

부품명(회로기호) Component(Part no.)	제조사(상표명) Manufacturer(Brand)	모델명(형식) Model(Type)	정격 또는 특성 Rating or Characteristics	인증마크 Tested by
(Alternate)	HUA JUNG COMPONENTS CO LTD	MKX1	Max. 0.68 μ F, min. 250 Vac. Min. 110 °C Class X1	ENEC
(Alternate)	XIAMEN FARATRONIC CO LTD	MKP65	Max. 0.68 μ F, min. 250 Vac. Min. 110 °C Class X1 or X2	VDE
(Alternate)	KEMET ELECTRONICS ITALIA SRL	F872	Max. 0.68 μ F, min. 250 Vac. Min. 110 °C Class X1	ENEC
(Alternate)	CHIEFCON ELECTRONICS CO LTD	CKX	Max. 0.68 μ F, min. 250 Vac. Min. 110 °C Class X2.	ENEC
(Alternate)	Ultra Tech Xiphi Enterprise Co. Ltd.	HQX	Max. 0.68 μ F, min. 250 Vac. Min. 110 °C Class X2.	VDE
(Alternate)	Hua Jung Components Co Ltd	MKP	Max. 0.68 μ F, min. 250 Vac. Min. 110 °C Class X2.	ENEC
(Alternate)	Carli Electronics, Co., Ltd.	MPX	Max. 0.68 μ F, min. 250 Vac. Min. 110 °C Class X1 or X2.	VDE
(Alternate)	NISTRONICS (JIANGXI) CO LTD	MPY	Max. 0.68 μ F, min. 250 Vac. Min. 110 °C Class X1.	VDE
Y-Capacitors (C3, C4, C21) (Optional) (C3, C4: Max. 1000 pF, C21: Max. 470 pF)	TDK Corporation	CS	min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	TDK Corporation	CD	min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Walsin Technology Corp.	AC	min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Walsin Technology Corp.	AH	min. 250 V, min. 125 °C, class Y1	VDE

부품명(회로기호) Component(Part no.)	제조사(상표명) Manufacturer(Brand)	모델명(형식) Model(Type)	정격 또는 특성 Rating or Characteristics	인증마크 Tested by
(Alternate)	Walsin Technology Corp.	AS	min. 250 V, min. 125 °C, class Y1	VDE
(Alternate)	Xiamen Wanming Electronics Co., Ltd.	HM, HJ	min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Huiwan	AB	min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Huiwan	AR	min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	VISHAY Electronic GmbH	VY1	min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Murata Mfg. Co., Ltd.	KX	min. 250 V, min. 125 °C, class Y1 or Y2	VDE
Y-Capacitors (C22, C23, C30) (Optional) (C22, C23: Max. 2200 pF, C30: Max. 1000 pF)	Walsin Technology Corp.	AH	min. 250 V, min. 125 °C, class Y1	VDE
(Alternate)	XIAMEN WANMING ELECTRONICS CO LTD	CK/CM/SD	min. 250 V, min. 125 °C, class Y1	ENEC
(Alternate)	SICHUAN TRX TECHNOLOGY CO., LTD	TRX	min. 400 V, min. 125 °C, class Y1 or Y2	ENEC
(Alternate)	ANSHAN KEIFAT ELECTRONIC CERAMIC TECHNICAL CO LTD	CT7	min. 250 V, min. 125 °C, class Y1 or Y2	VDE
Bridge Capacitor (C31, C32) (Optional)	Walsin Technology Corp.	AH	Max. 1500 pF, min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	XIAMEN WANMING ELECTRONICS CO LTD	CK/CM/SD	Max. 1500 pF, min. 250 V, min. 125 °C, class Y1 or Y2	ENEC
(Alternate)	SICHUAN TRX TECHNOLOGY CO., LTD	TRX	Max. 1500 pF, min. 400 V, min. 125 °C, class Y1 or Y2	ENEC

부품명(회로기호) Component(Part no.)	제조사(상표명) Manufacturer(Brand)	모델명(형식) Model(Type)	정격 또는 특성 Rating or Characteristics	인증마크 Tested by
(Alternate)	ANSHAN KEIFAT ELECTRONIC CERAMIC TECHNICAL CO LTD	CT7	Max. 1500 pF, min. 250 V, min. 125 °C, class Y1 or Y2	VDE
Photo Coupler (U3, U4, U9)	VISHAY SEMICONDUCTOR GMBH	TCLT1008	Dti ≥ 0.4 mm Int., dcr = 8.0 mm Ext. dcr ≥ 8.0 mm, thermal cycling test, 110 °C	VDE
(Alternate)	EVERLIGHT ELECTRONICS CO LTD	EL817(SMD type)	Dti ≥ 0.4 mm Int., dcr = 8.0 mm Ext. dcr ≥ 7.6 mm, thermal cycling test, 110 °C	VDE
(Alternate)	Ct Microelectronics Far East Ltd	CT817C(V)(SL)(T)- HG	Dti ≥ 0.4 mm Int., dcr = 8.0 mm Ext. dcr > 8.1 mm, thermal cycling test, 110 °C	VDE
(Alternate)	Lite-on Technology Corp	LTV-1008	Dti ≥ 0.4 mm Int., dcr = 8.0 mm Ext. dcr ≥ 8.0 mm, thermal cycling test, 115 °C	VDE
(Alternate)	Ct Microelectronics Far East Ltd	CT1018(V)(T)-W	Dti ≥ 0.4 mm Int., dcr ≥ 8.0 mm Ext. dcr ≥ 8.2 mm 125 °C	VDE
(Alternate)	Lite-on Technology Corp	LTV-817S	Dti ≥ 0.4 mm Int., dcr ≥ 8.0 mm Ext. dcr ≥ 7.0 mm 115 °C	VDE
Varistors (ZNR1) (Optional)	Centra Science	CNR-14D471K	300 Vac, 385 Vdc, 105 °C	VDE
(Alternate)	Joyin Co., Ltd.	JVT14S471K JVT14N471K	300 Vac, 385 Vdc, 125 °C	VDE
(Alternate)	Joyin Co., Ltd.	JVZ14N471K	300 Vac, 385 Vdc, 105 °C	VDE
(Alternate)	Thinking Electronic Industrial Co., Ltd.	TVR14471	300 Vac, 385 Vdc, 105 °C	VDE
(Alternate)	Thinking Electronic Industrial Co., Ltd.	TVR14471-M	300 Vac, 385 Vdc, 105 °C	VDE
(Alternate)	Thinking Electronic Industrial Co., Ltd.	TVR14471-D	300 Vac, 385 Vdc, 105 °C	VDE

부품명(회로기호) Component(Part no.)	제조사(상표명) Manufacturer(Brand)	모델명(형식) Model(Type)	정격 또는 특성 Rating or Characteristics	인증마크 Tested by
(Alternate)	Thinking Electronic Industrial Co., Ltd.	TVR14471-V	300 Vac, 385 Vdc, 105 °C	VDE
(Alternate)	Guangdong Huiwan Electronics, Technology Co., Ltd.	V-471K-14D(E)H	300 Vac, 385 Vdc, 125 °C	VDE
(Alternate)	Xiamen Wanming Electronics Co., Ltd.	WMR14D471K-2	300 Vac, 385 Vdc, 105 °C	VDE
(Alternate)	Xiamen Wanming Electronics Co., Ltd.	WMR14D471K-3	300 Vac, 385 Vdc, 125 °C	VDE
Transformer (T1)	MEAN WELL Enterprise Co., Ltd.	TF-8017 for XDR-960E-24ZZZZ TF-8018 for XDR-960E-36ZZZZ TF-8019 for XDR-960E-48ZZZZ	Class F	Tested with appliance
Transformer (T2)	MEAN WELL Enterprise Co., Ltd.	TF-8040	Class B	Tested with appliance
Line Choke (LF1) (Optional)	MEAN WELL Enterprises Co., Ltd.	TR-1055	Rated min. 155 °C	Tested with appliance
Line Choke (LF2) (Optional)	MEAN WELL Enterprises Co., Ltd.	TR-1224	Rated min. 155 °C	Tested with appliance
Choke (L1) (Optional)	MEAN WELL Enterprises Co., Ltd.	TF-8021	Rated min. 155 °C	Tested with appliance
Choke (L2) (Optional)	MEAN WELL Enterprises Co., Ltd.	TF-8020	Rated min. 155 °C	Tested with appliance
Choke (L5) (Optional)	MEAN WELL Enterprises Co., Ltd.	TR-1056	Rated min. 155 °C	Tested with appliance
Choke (L6, L7) (Optional)	MEAN WELL Enterprises Co., Ltd.	TR-1053	Rated min. 155 °C	Tested with appliance
Bleeder Resistor (R1, R2)	TZAI YUAN Enterprise Co., Ltd.	SMD***** HSMD*****	Each Max. 240 kΩ min. 1/4 W	CB by UL
(Alternate)	WALSIN TECHNOLOGY CORP	WF Series	Each Max. 240 kΩ min. 1/4 W	CB by UL

부품명(회로기호) Component(Part no.)	제조사(상표명) Manufacturer(Brand)	모델명(형식) Model(Type)	정격 또는 특성 Rating or Characteristics	인증마크 Tested by
(Alternate)	Ever Ohms Technology Co Ltd	HR Series	Each Max. 240 kΩ min. 1/4 W	CB by UL
(Alternate)	Guangdong Fenghua Advanced Technology Holding Co., Ltd	RS-06 Series	Each Max. 240 kΩ min. 1/4 W	CB by Nemko
(Alternate)	Guangdong Fenghua Advanced Technology Holding Co., Ltd	RVS	Each Max. 240 kΩ min. 1/4 W	CB by Nemko
(Alternate)	Uniroyal Electronics Global Co Ltd	HV06	Each Max. 240 kΩ min. 1/4 W	CB by UL
(Alternate)	Viking Tech Corporation Kaoshiung Branch	HVR	Each Max. 240 kΩ min. 1/4 W	CB by UL
(Alternate)	Viking Tech Corporation Kaoshiung Branch	HVRC	Each Max. 240 kΩ min. 1/4 W	CB by UL
(Alternate)	Viking Tech Corporation Kaoshiung Branch	HVR05, HVR0A, HVR12 series	Each Max. 240 kΩ min. 1/4 W	CB by UL
Relay (RY1)	Sanyou Corporation Limite	SJ-S-112DMH-F	Rated 10 A, 250 VAC 105 °C	VDE
(Alternate)	Tyco Electronics (Shenzhen) Co Ltd	OJS-SS-112HEF	Rated 16 A, 250 VAC 105 °C	TUV
(Alternate)	Xiamen Hongfa Electroacoustic Co., Ltd.	HF46F-G/12-HS1T	Rated 7 A, 250 VAC 105 °C	VDE
Relay (RY100)	Xiamen Hongfa Electroacoustic Co.,Ltd.	HFD23/012-1ZS	Rated 1 A, 30 Vdc	TUV
(Alternate)	Sanyou Corporation Limited	SYS-S-112L	Rated 1 A, 125 Vac	TUV
(Alternate)	Xiamen Hongfa Electroacoustic Co.,Ltd.	HFD4	Rated 1 A, 30 Vdc	TUV
Thermal Switch (TSW1, TSW2)	SEKI	ST-22	Rated min. 105 °C – 120 °C	VDE, KC
(Alternate)	Baoying Safty Electronic Technology Co Ltd	BW-DCP, BW-B	Rated min. 105 °C – 120 °C	VDE

부품명(회로기호) Component(Part no.)	제조사(상표명) Manufacturer(Brand)	모델명(형식) Model(Type)	정격 또는 특성 Rating or Characteristics	인증마크 Tested by
(Alternate)	YANGZHOU BAOZHU ELECTRIC APPLIANCE CO LTD	TB02	Rated min. 105 °C – 120 °C	TUV

☐ 유의사항 (Attention) :

1. 안전관리부품은 전기적인 안전에 직접적인 영향을 주는 부품으로서 안전인증기관이 정기공장검사 시 확인 관리 하는 사항입니다. 따라서 상기목록에 기재된 사항을 변경하거나 또는 복수등재를 원하시는 경우는 안전인증기관에 인증변경신청을 하여야 합니다.

As the "Critical components" are parts in directly related with safety, these components shall be checked during a factory inspection by the certification body. In case of applying multiple listing or changing the items above, the certification revision shall be applied.

2. 인증변경신청 없이 임의로 변경하는 경우는, 전기용품 및 생활용품 안전관리법 시행규칙 제 21 조제 1 항 또는 제 38 조제 1 항 규정에 의한 안전인증 취소 혹은 안전확인신고 효력상실 사유가 됨을 유의하시기 바랍니다.

The Safety Certification will be cancelled under the Article 21(1), 38(1) of the Enforcement Rule of the Electrical appliances and Consumer Products Safety Control Act if the contents of the Certification is altered without our authorization.

FP511-04-01

□ 첨부 2 : 기본모델 · 파생모델의 내용
Description of the basic and series model

파생모델명 Derivative model	기본모델과의 차이점 Differences between the basic and derivative model(s)
XDR-960E-48PI	It is identical to basic model except for model designation.
XDR-960E-48LA	It is identical to basic model except for model designation.
XDR-960E-48KC	It is identical to basic model except for model designation.
XDR-960E-48PIKC	It is identical to basic model except for model designation.
XDR-960E-48LAKC	It is identical to basic model except for model designation.
XDR-960E-24	It is identical to basic model except for model designation, output ratings, turns of secondary windings for Transformer (T1). (Output: 24 Vdc, 40 A; Vo Adj.: 24-29 Vdc, Max. 960 W)
XDR-960E-24PI	It is identical to basic model except for model designation, output ratings, turns of secondary windings for Transformer (T1). (Output: 24 Vdc, 40 A; Vo Adj.: 24-29 Vdc, Max. 960 W)
XDR-960E-24LA	It is identical to basic model except for model designation, output ratings, turns of secondary windings for Transformer (T1). (Output: 24 Vdc, 40 A; Vo Adj.: 24-29 Vdc, Max. 960 W)
XDR-960E-24KC	It is identical to basic model except for model designation, output ratings, turns of secondary windings for Transformer (T1). (Output: 24 Vdc, 40 A; Vo Adj.: 24-29 Vdc, Max. 960 W)
XDR-960E-24PIKC	It is identical to basic model except for model designation, output ratings, turns of secondary windings for Transformer (T1). (Output: 24 Vdc, 40 A; Vo Adj.: 24-29 Vdc, Max. 960 W)
XDR-960E-24LAKC	It is identical to basic model except for model designation, output ratings, turns of secondary windings for Transformer (T1). (Output: 24 Vdc, 40 A; Vo Adj.: 24-29 Vdc, Max. 960 W)
XDR-960E-36	It is identical to basic model except for model designation, output ratings, turns of secondary windings for Transformer (T1). (Output: 36 Vdc, 26.6 A; Vo Adj.: 36-42 Vdc, Max. 957.6 W)
XDR-960E-36PI	It is identical to basic model except for model designation, output ratings, turns of secondary windings for Transformer (T1). (Output: 36 Vdc, 26.6 A; Vo Adj.: 36-42 Vdc, Max. 957.6 W)
XDR-960E-36LA	It is identical to basic model except for model designation, output ratings, turns of secondary windings for Transformer (T1). (Output: 36 Vdc, 26.6 A; Vo Adj.: 36-42 Vdc, Max. 957.6 W)
XDR-960E-36KC	It is identical to basic model except for model designation, output ratings, turns of secondary windings for Transformer (T1). (Output: 36 Vdc, 26.6 A; Vo Adj.: 36-42 Vdc, Max. 957.6 W)
XDR-960E-36PIKC	It is identical to basic model except for model designation, output ratings, turns of secondary windings for Transformer (T1). (Output: 36 Vdc, 26.6 A; Vo Adj.: 36-42 Vdc, Max. 957.6 W)
XDR-960E-36LAKC	It is identical to basic model except for model designation, output ratings, turns of secondary windings for Transformer (T1). (Output: 36 Vdc, 26.6 A; Vo Adj.: 36-42 Vdc, Max. 957.6 W)

제품특기사항 및 시험조건
Remarks & Test conditions

1. MoU NCB Review Report based on: (25-041150-01-2)
 - CB Certificate Ref. No.: JPTUV-173601 (TÜV Rheinland Japan Ltd.)
 - CB Test Report No.: CN252P5B 001 (TÜV Rheinland (Shanghai) Co., Ltd.)

2. Product Description:
 - Measured Power Consumption: 1009.6 W
 - Insulation Class: Class I
 - Protection against Ingress of water: IP20
 - Mass of Equipment: Approx. 1.7 kg

- * Factory(ies) information
 - MEAN WELL (Guangzhou) Electronics Co.,Ltd.
No.11 Jingu South Road, Huadu District, Guangzhou 510890, Guangdong, China
 - MEAN WELL ENTERPRISES CO., LTD.
No. 28 Wuquan 3rd Road, Wugu District, New Taipei City 248, Taiwan (R.O.C.)
 - Yongden Technology Corporation
345 MacArthur HighWay, Tabang, Guiguinto, Bulacan 3015, Philippines
 - MEAN WELL INDIA ELECTRONICS PRIVATE LIMITED
9C, Peenya industrial area, Chokkasandra, 2ND PHASE, PEENYA,
Beng aluru (Bangalore) Urban, Karnataka, 560058, India

☐ 본 제품의 검토내용에 관하여 문의하실 사항이 있으시면 아래 연락처로 문의하시기 바랍니다.
검토담당자 / 연락처 : 인증사업본부 인증융합센터 장 재용 / 055-791-3305

☐ If you have any question on product review, please contact the person below :
Job holder: Certification Business Division, Certification Convergence Center, J.Y.Jang / +82 55 791 3305

FP511-05-00

☐ 첨부 3 : 안전확인신고 내용의 변경 현황
Revisions Status

변경발급 내용 Contents of Certificate Revisions
Not applicable

FP511-06-00

☐ 첨부 : 제품사진
Photographs



