



UK Declaration of Conformity

For the following equipment:

Product Name: LED Driver

Model Designation:

XLC-25-12-S, XLC-25-24-S, XLC-25-12, XLC-25-24, XLC-25-H-ysz (y=Blank, B or DA2; s=Blank or S; z=Blank or

N; when y, s and z=blank, the last '-' will be omitted)

XLN-25-12, XLN-25-24, XLN-25-Hy (y=Blank, -B or -DA2)

XLC-40-12-S, XLC-40-24-S, XLC-40-12, XLC-40-40-H-ysz (y=Blank, B or DA2; s=Blank or S; z=Blank or

N; when y, s and z=blank, the last '-' will be omitted)

XLN-40-12, XLN-40-24, XLN-40-Hy (y=Blank, -B or -DA2) XLC-25-H-KNS,XLC-40-H-KNS,XLC-25-H-KN,XLC-40-H-KN

The designated product(s) is(are) in conformity with the relevant legislation:

The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012: SI 2012 No. 3032

Implementing measure COMMISSION REGULATION(EU) 2019/2020

The Ecodesign for Energy-Related Products and Energy Information (Amendment) (EU Exit) Regulations 2020

Electrical Equipment (Safety) Regulations 2016:

BS EN 61347-1:2015+A1 ENEC certificate No: HN 69291178 BS EN 61347-2-13:2014+A1 ENEC certificate No: HN 69291180

Electrical Compatibility Regulations 2016:

EMI (Electro-Magnetic Interference)

Conducted emission / Radiated emission

BS EN IEC 55015:2019+A11:2020

Harmonic current BS EN IEC 61000-3-2:2019+A1:2021 Class C Voltage flicker BS EN 61000-3-3:2013+A1:2019+A2:2021

EMS (Electro-Magnetic Susceptibility)

BS EN IEC 61547:2023	
ESD air	

ESD air	BS EN 61000-4-2:2009	Level 3	8KV
ESD contact	BS EN 61000-4-2:2009	Level 2	4KV
RF field susceptibility	BS EN IEC 61000-4-3:2020	Level 2	3V/m
EFT bursts	BS EN 61000-4-4:2012	Level 2	1KV Power Line
EFT bursts	BS EN 61000-4-4:2012	Level 2	0.5KV Control Line
Surge susceptibility	BS EN 61000-4-5:2014+A1:2017	Level 3	1KV/Line-Line
Conducted susceptibility	BS EN 61000-4-6:2014	Level 2	3V
Magnetic field immunity	BS EN 61000-4-8:2010	Level 2	3A/m
Valtana dia intermentian	DC EN IEC 64000 4 44:2000 - 700/ maid all alle	f 40	00/

Voltage dip, interruption BS EN IEC 61000-4-11:2020 70% residual voltage for 10 periods, 0% residual voltage for 0.5 periods Note: Component power supply will be operated with a final equipment. Since EMC performance will be affected by the complete

installation, the final equipment manufacturers must re-qualify EMC Regulations on the complete installation again. Tests above are only to be performed with LEDs.

For guidance on how to perform these EMC tests, please refer to TDF (Technical Documentation File).

This Declaration is effective from serial number GC5xxxxxxx

Person responsible for marking this declaration:

MEAN WELL Enterprises Co., Ltd.

(Manufacturer Name)

No.28, Wuquan 3rd Rd., Wugu Dist., New Taipei City 24891, Taiwan

(Manufacturer Address)

Eris Wu/ Director, Group R&D:

(Name / Position)

(Signature)

Alex Tsai/ Director, Product Strategy Center:

(Name / Position)

Taiwan

Jan. 15th, 2025

(Place)

(Date)

(Signature)